





# Rockdeck<sup>®</sup>

COLLECTION

202x302mm | 202x202mm | 96x202mm, 15mm  
600x600mm | 298x600mm | 298x298mm, 12mm

**Experience unyielding  
Durability**




Introducing

# Rockdeck Collection

**Designed to Withstand, Adversities and Trends.**

Discover the raw elegance of the Rockdeck Collection from Simpolo, where the timeless beauty of weathered rock formations meets cutting-edge innovation. These tiles are designed to capture the rugged splendor of natural terrains, with a surface that evokes the aged, weathered rock textures. Each piece in the collection offers unparalleled durability and a distinctive aesthetic that mirrors the weather-beaten charm of the natural world.

Engineered for exceptional performance, these tiles offer superior resistance to wear, stains, and extreme weather conditions, making them ideal for high-traffic areas and retreats. Their slip-resistant surface ensures safety without compromising on style, while their low-maintenance nature keeps them looking pristine with minimal effort. Transform your spaces with the functional elegance of Rockdeck, where every tile not only enhances your décor but also stands up to the demands of everyday life.





## Anti-Fall Surface

The unique Anti-fall surface categorized as R-10 surface is designed to prevent you from falling even on wet floors.

### Technical Features



Colour does not fade over time



Resistant to sudden temperature changes



Resistant to acid, chemicals, salt, etc.



Resistant to damage from mould and moss



Antislip



Quick and easy to install



Easy to remove



Extremely long-lasting



Installation with adhesive is possible



Highly resistant to loads



Strong & durable



Allows water drainage



4mm minimum joint



Easy to clean




Suitable for outdoor areas





## Tiny Rock Collection

12 Colours



202x  
302mm  
15mm

202x  
202mm  
15mm

96x  
202mm  
15mm

The Tiny Rock Collection features a palette of rustic colours, each inspired by the rich hues of natural stone. From the warm, inviting tones of Agra Camel to the earthy depth of Arde Rusty and the classic charm of Castle Cotta, these colours bring an authentic, timeless appeal to any space.

Whether you seek to evoke a cozy, rustic ambiance or make a bold design statement, the collection offers versatile shades that harmonize effortlessly with various décor styles. Each colour is meticulously crafted to enhance the natural beauty of your environment.

## Tiny Rock Collection

Floor. Agra Camel  
Anti-Fall  
202x302mm  
202x202mm  
96x202mm

Scan for Virtual  
360°



Application Area

# Backyard



### Agra Series



Agra Red 30 Random



30 Random



30 Random



Agra Camel 30 Random



30 Random



30 Random



Agra Sand 30 Random



30 Random




30 Random



V3



202x302mm  
Anti-Fall Surface  
15mm Thickness



202x202mm  
Anti-Fall Surface  
15mm Thickness



96x202mm  
Anti-Fall Surface  
15mm Thickness

• 4mm minimum joint  
is recommended

Application Area

# Front Yard




Floor. Arde Camel  
Anti-Fall  
202x302mm  
202x202mm  
96x202mm

Scan for Virtual  
360°



Tiny Rock Collection



## Arde Series



Arde Rusty 30 Random



30 Random



30 Random



Arde Camel 30 Random



30 Random



30 Random



Arde Dove 30 Random



30 Random



30 Random



202x302mm  
Anti-Fall Surface  
15mm Thickness



202x202mm  
Anti-Fall Surface  
15mm Thickness



96x202mm  
Anti-Fall Surface  
15mm Thickness

• 4mm minimum joint  
is recommended

Tiny Rock Collection

Application Area

Patio



Scan for Virtual  
360°



Floor. Ashlar Grey  
Anti-Fall  
202x302mm  
202x202mm  
96x202mm



## Ashlar Series



Ashlar Grey 30 Random



30 Random



42 Random



Ashlar Ash 30 Random



30 Random



42 Random



Ashlar Desert 30 Random



30 Random



42 Random



Anti-fall  
R-10




V3



202x302mm  
Anti-Fall Surface  
15mm Thickness



202x202mm  
Anti-Fall Surface  
15mm Thickness



96x202mm  
Anti-Fall Surface  
15mm Thickness

• 4mm minimum joint  
is recommended

Application Area

# Courtyard

Scan for Virtual  
360°



Tiny Rock Collection

Floor. Castle Cotta  
Anti-Fall  
202x302mm  
202x202mm  
96x202mm



## Castle Series



Castle Grey 16 Random




16 Random



16 Random



Castle Cotta 16 Random




16 Random



16 Random




Castle Tan 16 Random



16 Random




16 Random



V3



202x302mm  
Anti-Fall Surface  
15mm Thickness



202x202mm  
Anti-Fall Surface  
15mm Thickness



96x202mm  
Anti-Fall Surface  
15mm Thickness

• 4mm minimum joint  
is recommended



## Rockdeck Collection



600x  
600mm  
12mm

298x  
600mm  
12mm

298x  
298mm  
12mm

**20 Colours**

The Rockdeck Collection boasts a diverse colour and design lineup, each meticulously designed to capture the essence of natural rock. Featuring a range of earthy colours, from grays to warm beiges, these tiles evoke the authentic beauty of rugged landscapes.

With textures that mirror the weathered charm of rock, the collection provides a tactile experience as rich as its visual appeal. Its varied aesthetics ensure a versatile application, enhancing spaces with a robust and timeless elegance.

## Rockdeck Collection

### Wall. Clastic Grey

Anti-Fall

600x600mm / 298x600mm / 298x298mm

### Floor. Clastic Grey

Anti-Fall

600x600mm / 298x600mm / 298x298mm

Scan for Virtual  
360°




Application Area

# Pool Deck





### Clastic Series



Clastic Grey 12 Random



24 Random



48 Random



Clastic Silver 12 Random



24 Random



48 Random



Clastic Verde 12 Random



24 Random



48 Random



Clastic Pearl 12 Random




24 Random



48 Random



600x600mm  
Anti-Fall Surface  
12mm Thickness



298x600mm  
Anti-Fall Surface  
12mm Thickness



298x298mm  
Anti-Fall Surface  
12mm Thickness

• 4mm minimum joint  
is recommended



Scan for Virtual  
360°



Floor. Cottas Lime  
Anti-Fall  
600x600mm  
298x600mm  
298x298mm



### Cottas Series



Cottas Red 8 Random



16 Random



32 Random



Cottas Lime 8 Random



16 Random



32 Random



Anti-fall  
R-10

V3



600x600mm  
Anti-Fall Surface  
12mm Thickness



298x600mm  
Anti-Fall Surface  
12mm Thickness



298x298mm  
Anti-Fall Surface  
12mm Thickness

• 4mm minimum joint  
is recommended

Floor. Dewstone Ash  
Anti-Fall  
600x600mm  
298x600mm  
298x298mm

Scan for Virtual  
360°




Application Area

Porch



### Dewstone Series




Dewstone Ash 24 Random



48 Random



96 Random



Dewstone Silver 24 Random



48 Random



96 Random



Dewstone Lime 24 Random



48 Random



96 Random



600x600mm  
Anti-Fall Surface  
12mm Thickness



298x600mm  
Anti-Fall Surface  
12mm Thickness



298x298mm  
Anti-Fall Surface  
12mm Thickness

• 4mm minimum joint  
is recommended

Application Area

# Courtyard

Scan for Virtual  
360°



## Rockdeck Collection

Floor. Limos Lime  
Anti-Fall  
600x600mm  
298x600mm  
298x298mm





## Limos Series



Limos Grey 24 Random



48 Random



96 Random



Limos Dove 24 Random



48 Random



96 Random



Limos Silver 24 Random




48 Random



96 Random



Limos Lime 24 Random



48 Random



96 Random



600x600mm  
Anti-Fall Surface  
12mm Thickness



298x600mm  
Anti-Fall Surface  
12mm Thickness



298x298mm  
Anti-Fall Surface  
12mm Thickness

• 4mm minimum joint  
is recommended

Application Area

# Portico

Wall. **Salco Silver**  
Anti-Fall  
600x600mm  
298x600mm  
298x298mm


Floor. **Salco Silver**  
Anti-Fall  
600x600mm  
298x600mm  
298x298mm

Scan for Virtual  
360°





### Salco Series



Salco Grey 18 Random



36 Random



72 Random



Salco Silver 18 Random



36 Random



72 Random



Salco Barley 18 Random




36 Random



72 Random



Salco Cream 18 Random



36 Random



72 Random

Anti-fall  
R-10



600x600mm  
Anti-Fall Surface  
12mm Thickness



298x600mm  
Anti-Fall Surface  
12mm Thickness



298x298mm  
Anti-Fall Surface  
12mm Thickness

• 4mm minimum joint  
is recommended

Rockdeck Collection

Application Area

**Sun Deck**

Floor. **Sediment Brown**  
Anti-Fall  
600x600mm  
298x600mm  
298x298mm

Scan for Virtual  
360°





### Sediment Series



Sediment Grey 15 Random



30 Random



60 Random



Sediment Brown 15 Random



30 Random



60 Random



Sediment Cream 15 Random



30 Random



60 Random



600x600mm  
Anti-Fall Surface  
12mm Thickness



298x600mm  
Anti-Fall Surface  
12mm Thickness




298x298mm  
Anti-Fall Surface  
12mm Thickness


• 4mm minimum joint  
is recommended

# Laying Patterns


## Tiny Rock Collection




202x302mm | 202x202mm  
96x202mm




202x302mm | 202x202mm  
96x202mm




202x302mm | 202x202mm  
96x202mm



202x302mm | 202x202mm  
96x202mm




202x302mm | 202x202mm  
96x202mm




202x302mm | 202x202mm  
96x202mm

The versatile and multiple sizes of the collection allow you to craft floors using different laying patterns. The collection offers the same designs in different sizes for creative and functional needs.


## Rockdeck Collection




600x600mm - 57% | 298x600mm - 29%  
298x298mm - 14%




600x600mm - 57% | 298x600mm - 29%  
298x298mm - 14%




600x600mm - 40% | 298x600mm - 40%  
298x298mm - 20%



600x600mm - 45% | 298x600mm - 45%  
298x298mm - 10%



600x600mm - 57% | 298x600mm - 29%  
298x298mm - 14%



600x600mm - 67% | 298x600mm - 17%  
298x298mm - 16%

\*Tiny Rocks layouts are made possible as per standard ratio of 1:1:1 of each size which is as per packing standard.

In Rockdeck layouts we show the percentage as per square meter.

## Technical Specifications

CHARACTERISTIC	STANDARD AS PER ISO13006:2018/ EN14411 Gr.Bla		METHOD OF TESTING	MEAN VALUE OF SIMPOLO	
<b>Regulatory Properties</b>	Un-Rectified Rectified	Un-Rectified Rectified	ISO 10545-2	Un-Rectified Rectified	
*Deviation in Length and Width	±0.60 % (±2.0 mm)	±0.30 % (±1.00 mm)	ISO 10545-2	±0.60 % (±2.0 mm) ±0.30 % (±1.00 mm)	
*Deviation in Thickness	±5.0 % (± 0.50 mm)	±5.0 % (± 0.50 mm)	ISO 10545-2	±5.0 % (± 0.50 mm) ±5.0 % (± 0.50 mm)	
*Straightness in Side	±0.50 % (± 1.5 mm)	±0.30 % (± 0.80 mm)	ISO 10545-2	±0.50 % (± 1.5 mm) ±0.30 % (± 0.80 mm)	
*Rectangularity	±0.50 % (± 2.0 mm)	±0.30 % (± 1.50 mm)	ISO 10545-2	±0.50 % (± 2.0 mm) ±0.30 % (± 1.50 mm)	
*Surface Flatness Central Curvature	±0.50 % (± 2.0 mm)	±0.40 % (± 1.80 mm)	ISO 10545-2	±0.50 % (± 2.0 mm) ±0.40 % (± 1.80 mm)	
*Surface Flatness Edge Curvature	±0.50 % (± 2.0 mm)	±0.40 % (± 1.80 mm)	ISO 10545-2	±0.50 % (± 2.0 mm) ±0.40 % (± 1.80 mm)	
*Surface Flatness Warpage	±0.50 % (± 2.0 mm)	±0.40 % (± 1.80 mm)	ISO 10545-2	±0.50 % (± 2.0 mm) ±0.40 % (± 1.80 mm)	
Surface Quality	>95% defects free		ISO 10545-2	>95% defects free	
Small Colour Difference (For Plain Colour)	ΔE <1.0		ISO 10545-16	ΔE <0.80	
<b>Structural Properties</b>					
Water Absorption	Ev≤0.50 % Individual Max:0.6%		ISO 10545-3	Max 0.2 %	
Bulk Density	As per Manufacturer		ISO 10545-3	> 2.28 gm/cc	
<b>Massive Mechanical Properties</b>					
Modulus of Rupture (12mm, 16mm, 20 mm)	Min. 35.0 N/mm <sup>2</sup>		ISO 10545-4	Min. 40.0 N/mm <sup>2</sup>	
Breaking Strength Thickness ≥7.5 mm (12mm)	Min 1300.0 N		ISO 10545-4	Min 2000 N	
Breaking Strength Thickness ≥7.5 mm (15/16mm)	Min 1300.0 N		ISO 10545-4	Min 3000.0 N	
<b>Surface Mechanical Properties</b>					
MOH'S Hardness #	As per Manufacturer		BS EN 15771	Matt Min 6	
Surface Abrasion Resistance #	As per Manufacturer		ISO 10545-7	Matt Min PEI-3	
<b>Thermal Hygroscopic Properties</b>					
Moisture Expansion	Max 0.06% (0.6 mm/m)		ISO 10545-10	Max 0.02 mm/m	
Thermal Expansion(COE) at 100°C	As per Manufacturer		ISO 10545-8	Max. 6.0 x 10 <sup>-6</sup>	
Thermal Shock Resistance	Min 10 Cycle		ISO 10545-9	Min 10 Cycle	
Impact Resistance(COR) #	Min. 0.55		ISO 10545-5	Min 0.55	
Frost Resistance	As per Manufacturer		ISO 10545-12	Frost Proof	
<b>Chemical Properties</b>					
Resistance to Staining Glazed	Min. Class 3		ISO 10545-14	Min. Class 3	
Resistance to Household Chemicals & Swimming Pool Salts Glazed	Min Class GB		ISO 10545-13	Min Class GB	
Resistance to Low Concentrate Acid and Alkalies Glazed	As per Manufacturer		ISO 10545-13	Min Class GLB***	
Resistance to High Concentrate Acid and Alkalies Glazed	As per Manufacturer		ISO 10545-13	Min Class GHB***	
<b>Safety Properties</b>					
Skid Resistance - (DCOF-WET PENDULUM)##	As per Manufacturer		ASTM E-303	> 0.4	
Slip Resistance -Satin/ Matt (DCOF- R Value )##	As per Manufacturer		DIN 51130	Min R10	
Lead and Cadmium release	As per Manufacturer		ISO-10545-15	Does not yield Pb & Cd	

\* Whichever is Lower

\*\* With nano technology (Polished Vitrified tiles) Depending on Application area (low or high intensity of traffic)

\*\*\* Except Hydrofluoric Acid & its compound

# Tiles Intended for use on floor

## For Floor tiles, as per customer requirement

## Packing Detail

PRODUCT	ACTUAL SIZES	THICKNESS	TILES / BOX	COVERAGE AREA / BOX
<b>Tiny Rock &amp; Collection</b>	202x302mm (Un-Rect) - 4 pcs.	15mm		
	202x202mm(Un-Rect) - 4 pcs.	15mm	12 pcs.	0.484 m <sup>2</sup>
	96x202mm(Un-Rect) - 4 pcs.	15mm		5.216 ft <sup>2</sup>
<b>Rockdeck Collection</b>	600x600mm (Rect)	12mm	3 pcs.	1.08 m <sup>2</sup>
	298x600mm (Rect)	12mm	4 pcs.	0.72 m <sup>2</sup>
	298x298mm (Rect)	12mm	7 pcs.	0.62 m <sup>2</sup>
				11.63 ft <sup>2</sup>
				7.70 ft <sup>2</sup>
				6.69 ft <sup>2</sup>

**Simpolo Vitrified Private Limited**

Old Ghuntu Road, Morbi – 363 642 Gujarat, INDIA  
Tele.: +91 2822 241622, E-mail: [customercare@simpolo.net](mailto:customercare@simpolo.net)

**MUMBAI**

Simpolo Gallery, Unit No.: 203, 2nd Floor, Morya Land Mark 2, Link Road, Andheri (W), Mumbai – 400 053.  
Tele.: +91 22401 67131, E-mail: [mumbai@simpolo.net](mailto:mumbai@simpolo.net)

**AHMEDABAD**

1st Floor, 103, Sumel – 2, Near Gurudwara, S. G. Highway, Bodakdev, Ahmedabad – 380 054.  
Mob.: +91 79400 37222, +91 79400 52220, E-mail: [ahmedabad@simpolo.net](mailto:ahmedabad@simpolo.net)

**DELHI**

H – 139, First Floor, Sector – 63, Noida – 201 301, Uttar Pradesh.  
Mob.: +91 93103 90046, E-mail: [delhi@simpolo.net](mailto:delhi@simpolo.net)

**COCHIN**

33/2380 A-A1 NH Bypass, Vysali Bus Stop, Chakkaraparambu, Cochin – 682 032.  
Mob.: +91 93493 39938, Fax: +91 48440 37118, E-mail: [cochin@simpolo.net](mailto:cochin@simpolo.net)

**KOLKATA**

5th Floor, DD-27, Salt Lake City, Sector 1, Near Salt Lake City Center, Kolkata – 700 064. (W.B.)  
Mob.: +91 90733 53728, E-mail: [kolkata@simpolo.net](mailto:kolkata@simpolo.net)

**CHENNAI**

5th Floor, Prashanth Gold Tower, No. 39, North Usman Road, T. Nagar, Chennai – 600 017.  
Mob.: +91 9925251848, E-mail: [chennai@simpolo.net](mailto:chennai@simpolo.net)

**LUCKNOW**

Aditya Tower, 1st Floor, CP-8 Vijyant Khand, Gomati Nagar, Lucknow – 226010.  
Mob.: +91 97252 79749, E-mail: [lucknow@simpolo.net](mailto:lucknow@simpolo.net)

**BENGALURU**

2th Floor, 15th Cross Road, Outer Ring Rd, 5th Phase, J. P. Nagar, Bengaluru, Karnataka – 560078.  
Mob.: +91 9909418222, E-mail: [Bengaluru@simpolo.net](mailto:Bengaluru@simpolo.net)